

Easy disassembly

You won't believe how easy it is. The frame separates in seconds with the pull of a handle.

Transportation

The solo goes where you go. It's easy to handle and load. The heaviest piece weighs only 42 pounds.

Aluminum frame

Aluminum gives the Solo more strength with less weight - and no rust.

Powerful

24-volt DC motor combined with rear wheel drive provides plenty of power to go where you want to go.

Shown with optional wheel covers

Transaxle drive

Available in either the standard chain drive or an ultra-quiet, fully-enclosed transaxle drive.

Tiller adjustment

The control is at your fingertips, so there's no need to bend over to adjust the tiller angle. It's as easy to adjust as the tilt steering wheel on your car. Features four positive-locking positions.

Easy to use

Full variable speed control provides smooth starting and stopping. A dial control allows you to set your maximum speed. The electromechanical brake comes on automatically when you stop, and releases automatically when you start. A key lock is provided for security.



SPECIFICATIONS

white

Available in:

red

taupe

Overall length	45.5"
Overall width	24"
Weight of heaviest part	42 lbs.
Total weight (less batteries)	108 lbs.
Maximum speed	5 mph forward 3 mph reverse
Distance per charge	up to 20 miles*
Ground clearance (with 10" rear tires)	4"
Maximum weight of operator	300 lbs. 400 lbs. with heavy duty opt
Seat height: manual adjustment	17" - 18" - 19" - 20"

* with 150-lb. rider on level, hard surface.

Note: Ranger reserves the right to change specifications without notice.

EASY DISASSEMBLY



Remove seat.



Remove batteries.



3. Pull "T" handle.



Ready for loading.

Ranger All Season Corp.

PO Box 132 George, Iowa 51237 800-225-3811 • 712-475-2811

Proudly made in the U.S.A. • Visit us on the Internet: www.rangerallseason.com

U.S. Patent no's. 5,150,762 and 5,238,082

Your Ranger Dealer: